Call For SPECIAL PRICING 828-283-1999 Johnson-Wholesale



Equipment Catalog 2018





Equipment Engineered for Quality Work at High Speed FOR VCT/ CONCRETE / TERRAZZO FLOORS





EQUIPM ENT CATALOG

TABLE OF CONTENTS

TABLE OF CONTENTS	PAGE2
ABOUTAZTEC	PAGE3
VCT FLOOR EQUIPMENT	
WORKSMART [™] STRIP SYSTEM	PAGE 4-9
Step 1: Liquidator	PAGE5
Step 2: Sidewinder	PAGE6
Step 3: Edgewinder Edger	PAGE7
Step 4: Guzzler	PAGE 8
Step 5: Grand Finale	PAGE 9
WORKSMART [™] MAINTENANCE SYSTEM	PAGE 10-12
Low Rider Burnisher	PAGE 10-11
ProScrub Autoscrubber	PAGE 12
WORKSMART [™] REFRESHER SYSTEM	PAGE 13
WORKSMART [™] CONCRETE SYSTEM	PAGE 14-17
ULTRAGRIND	PAGE 15
ULTRAEDGE	PAGE 16
ULTRAVAC	PAGE 17
CONCRETE TRAINING CERTIFICATION	PAGE 18
AZTEC DIAMONDS	PAGE 19
CONCRETE CHEMICALS	PAGE 20
INDUSTRY ASSOCIATIONS	PAGE 21
GREEN CERTIFICATIONS	PAGE 21-26





201 Commerce Drive, Montgomeryville, PA 18936

www.aztecproducts.com � (800) 331-1423

FAMILY OWNED, AMERICAN MADE

Aztec is a family-owned USA manufacturer of concrete polishing and resurfacing machines and converter of gasoline engines to LPG for other equipment manufacturers.

GREEN CERTIFICATIONS

All equipment and engine conversions are proudly made in the USA, with CE, EPA, CARB, LEED and GS-42 certifications.

CONCRETE TRAINING CERTIFICATIONS

Aztec's Concrete Training Certification programs are offered 3x/year providing hands on experience in crack repair, surface prep, grinding, polishing, refreshing, coloring and maintaining concrete floors. Training is open to contractors, distributors, product reps, and anyone who wants to learn more about the lucrative possibilities for concrete floors.

CONCRETE DIAMONDS

Buy concrete diamonds on Aztec's sponsored website, <u>www.concretediamonds.com</u>.

SOCIAL MEDIA

Follow Aztec on Facebook, Instagram, LinkedIn, Twitter and YouTube!



AZTEC PRODUCTS 201 COM MERCE DRIVE MONTGOM ERYVILLE, PA 18936





The ONLY Complete Strip and Wax System

WORKSMART[™] STRIP SYSTEM

STEP 1: Apply Strip Solution with the Liquidator

Apply strip solution up to 45,000 sqft/hr with the Liquidator. Includes a 36 gallon (136L) solution tank and an adjustable applicator width of 26" to 52" (66cm-132cm).





STEP 2: Strip Floors with the Sidewinder

The Sidewinder's unique planetary drive and 3 counter-rotational brushes will strip 15,000 sqft/hr. At that speed the Sidewinder is 10x faster than a corded electric machine and 3x faster than a battery powered machine. The Sidewinder will strip up to 7 layers of wax in one pass.

STEP 3: Strip Finish under Gondolas and Hard to Reach Areas

The Edgewinder is a propane powered edger with less than 4" (10 cm) high deck and 26" (64 cm) reach, to get back deep in under racks, gondolas and shelving. Strips up to 50 linear feet per minute.





STEP 4: Retrieve Strip Solution with the Guzzler

The Guzzler retrieves 30,000 sqft/hr at walking speed. This easy to use system will squeegee a floor 3x faster than a wet vac or autoscrubber.

ED American

www.aztecproducts.com * (800) 331-1423 * (215) 393-4700 * FAX (215) 393-4800

STEP 5: Apply the Finish with the Grand Finale

The Grand Finale applicator reduces chemical usage by 30% and applies finish at up to 35,000 sqft/hr. No puddles, dry spots or streaking thanks to the Grand Finale's battery powered precision release system.



aztecproducts.com



4

The Liquidator

WORKSMART[™] STRIP SYSTEM —STEP 1

OZTE®

Solution Applicator with 36 Gallon (136 L) Capacity



www.aztecproducts.com * (800) 331-1423 * (215) 393-4700 * FAX (215) 393-4800

OZtes The Sidewinder

WORKSMART[™] STRIP SYSTEM —STEP 2

Sidewinder Propane Floor Stripper and Scrubber

The Sidewinder's three individually powered brushes strip at unmatched speed and aggressiveness. The propane powered Sidewinder is available in 24" (61 cm) and 30" (76 cm).

FAST:

Strip 15,000 sqft/hr (1393 m²/h) Scrub 30,000 sqft/hr (2787 m²/h) 10x faster than corded electric 3x faster than an autoscrubber 1.5x faster than battery powered

AGGRESSIVE:

Unique planetary scouring action plus heavy brush pressure results in high productivity with

productivity v no side torque.



EFFICIENT:

Save labor — eliminate up to 8 hours of labor expense compared to corded electric equipment.



- Strips 7-10 layers of finish in just one pass
- Rugged, all steel construction
- Planetary brush drive eliminates strip shadows and side torque
- Unique floating head design allows brushes to address irregular surfaces
- Brush RPM speed combined with up to 288 lbs. (130 kg) of head pressure delivers fast, deep stripping or scrubbing
- Standard centrifugal clutch substantially increases belt life
- Transport wheel for easy loading and maneuvering
- Additional 8 gallon (30.3L) water tank available upon request
- Available in 24" (61 cm) and 30" (76 cm) models
- Green certifications: EPA, CARB, LEED, CE, GS-42
- Optional engine meeting Blue Sky standards



OZTE® The Edgewinder

WORKSMART[™] STRIP SYSTEM —STEP 3

Low Profile Propane Edger for Hard to Reach Areas

LOW PROFILE

Edging with less than 4" (10 cm) high deck and 26" (66 cm) reach allows the Edgewinder to get back deep in under racks, gondolas, and shelving

AGGRESSIVE

Strip up to 50 linear feet per minute with the 14" (36 cm) diameter Stratagrit brush to dig out years of accumulated floor finish. Easily cuts through layers of edge build up. Strips at a walking pace.

HARD TO REACH PROBLEM SOLVER

GEWINDE

Floating flexible guard contains strip solution, allows close contact with walls, shelving legs, corners, and other tight areas.

SAFE FOR INDOOR USE

Powered by 13hp PurePower by Aztec 390 Series propane engine with battery key start. Custom engineered catalytic muffler is EPA, CARB, LEED certified.

ID# 017-02

- Floating flexible guard contains strip solution, allows close contact with walls, shelving legs, corners, and other tight areas
- Custom engineered catalytic muffler
- Pure Power by Aztec 390 Series engine with battery key start
- Green certifications: EPA, CARB, LEED, CE, GS-42
- Optional engine meeting Blue Sky standards





The Guzzler

WORKSMART[™] STRIP SYSTEM —STEP 4

Solution Retriever with 36 Gallon (136 L) Capacity



EFFICIENT

Up to 50% faster than other conventional recovery methods with no de-foamer required.

FAST

Twice the speed of an autoscrubber, with а 30" (76cm) squeegee path retrieves solution up to 30,000 sqft/hr (2787 m²/h).



PORTABLE

Dry weight of 65 lbs (30kg). Compact size and easy to maneuver.





The Grand Finale

WORKSMART[™] STRIP SYSTEM —STEP 5



PRODUCTIVITY ON VCT, CONCRETE AND TERRAZZO

VCT Floor Finish: 23,500 - 35,000 sqft/hr (2183-3252 m²/h)

Concrete Densifiers, Hardeners and Sealers: 16,500 - 25,000 sqft/hr (1533-2322 m²/h)

Water or Solvent-Based Concrete Coating: 13,500 - 20,000 sqft/hr (1254-1858 m²/h)

- 8X faster than a mop and bucket
- Reduce chemical usage by 30%
- Works with most floor finish up to 40% solid
- Portable, lightweight and durable
- Adjustable pressurized application flow
- Battery run time of 5-7 hours

- Quick and easy clean up
- Includes (1) microfiber and (1) looped mop head for multi-purpose uses and applications
- Head assembly available in 24" (61 cm) and 36" (91.5 cm)
- Spray nozzle with flexible hose upgrade now available to access smaller areas





The Low Rider

WORKSMART[™] MAINTENANCE SYSTEM

Low Rider Propane Burnisher

High Speed Propane Burnishers for Daily Maintenance of VCT and Polished Concrete Floors



LOWEST emissions in the industry^{*}, the LowRider is the ultimate floor burnisher for maintaining VCT and polished concrete floors. Available in 21" (54cm), 24" (61cm) or 27" (69cm) pad sizes, with optional Dust Control or Spray Mist upgrades.

- Ultra Low Profile: 4" (10 cm) for burnishing hard to reach areas
- Rugged, patented solid steel body
- 12 volt battery key start
- Adjustable comfort handle with click-nlock throttle cable
- Advanced polymer composite pad driver
- Adjustable back wheels for controlled pad pressure

- Premium catalytic muffler for ultra low CARB and EPA emissions
- Low oil shut down and safety regulator fuel system
- Green certifications: EPA, CARB, LEED, CE, GS-42
- Optional engine meeting Blue Sky standards



*Source: www3.epa.gov/otaq/certdata.htm#smallsi



CZTE Cow Rider Upgrades

WORKSMART[™] MAINTENANCE SYSTEM

Low Rider Propane Burnisher Optional Upgrades



DUST CONTROL LOW RIDER

The LowRider Dust Control burnisher is for VCT, terrazzo and polished concrete floors.

Unique patent-pending vacuum system improves indoor air quality (IAQ) by containing air particulates, and an easy change floating dust skirt.

All LowRiders with dust control upgrade meet GS-42 and meets the US green

building council LEED IEQ credit 3.4 requirements.

Dust Control Guide Hose

ID# 070-27-LRS

SPRAY MISTLOW RIDER

- The LowRider Spray Mist burnisher is for spray burnishing and diamond pad polishing VCT, terrazzo and polished concrete floors.
- Diamond pads last longer
- Low moisture cleaning
- Longer time between VCT stripping and concrete sealing cycles
- Longer hard floor life
- Time & labor savings while removing ground in dirt, scuffs and minor scratches in performing daily and weekly maintenance
- Adjustable spray nozzle position allows for a variable width spray radius, reaching up to a 95-degree angle

Adjustable Precision Spray Tip





The ProScrub

OZICE

WORKSMART[™] MAINTENANCE SYSTEM

ProScrub 20" Automatic Scrubber

RUGGED ECONOMICAL DEPENDABLE

The ProScrub automatic floor scrubber wet scrubs and dry vacuums in one pass. The ProScrub is inexpensive and exceptionally simple to use and maintain. The 24-volt system delivers approximately 3 hours of run time when fully charged.

- 12 Gallon (45L) solution tank
- 15 Gallon (56L) recovery tank
- 3/4 hp Brush Motor/220 RPM
- 1/2 hp 24-volt vacuum motor
- 65 lb (29kg) scrubbing pressure
- Rugged stainless steel swivel casters
- Pad holder or brush available

- Reinforced 30" (76 cm) steel squeegee
- Easy access to key components for simple maintenance
- Stainless steel skirt hardware
- Tool-less squeegee removal for transport
- Power source 2-130 AH 12v deep cycle lead/acid batteries*

ID# 030-20

* AGM -battery package available



OZTE®

The Refresher

WORKSMART[™] REFRESHER SYSTEM

The Aztec Refresher System is a machine engineered with the operator in mind. The Refresher is heavy and rugged enough to handle the aggressive demands of honing and polishing concrete, yet light and mobile enough to be highly maneuverable and smooth running for hours of continuous use.

The Refresher Multifunction 4-Step Process

STEP 1: Stripping/Deep Scrubbing

Strip or deep scrub the floor to remove VCT floor finish, sealer or deeply ground-in soils. Many polished concrete, terrazzo and marble floors have been coated with VCT floor finish or sealer, reducing their luster and making them higher maintenance.

STEP 2: Honing

Hone the floor to remove scratches or sealers using the quick-change Velcro® driver with hybrid diamonds. These diamonds will cut more deeply than resins, but not as deeply as metal diamonds, allowing the scratches or sealers to be removed. NOTE: Do not use hybrids on marble floors.

STEP 3: Polishing

Polish the floor using the Velcro® drivers with resin puck diamonds or the Mighty-Lok® drive with diamond pads.

STEP 4: Burnishing

Apply guard and burnish the floor using the Mighty-Lok® head to accept burnishing pads or diamond impregnated pads. Burnish until the floor heats to 90F/





- Gimbled head follows floor resulting in consistent gloss
- Planetary motion flattens while polishing floor
- Self-leveling, mechanically sealed drive unit
- Synchronous positive drive belt with metal synchronous drive pulleys
- Solid-lube multi-directional bearings with Nylos seals
- Premium German precision centrifugal clutch and custom catalytic muffler
- Rugged powder-coated US steel frame & body
- 8 Gallon water tank for wet operations
- Green certifications: EPA, CARB, LEED, CE, GS-42
- Optional engine meeting Blue Sky standards

www.aztecproducts.com



The Concrete and Terrazzo Floor System

WORKSMART[™] CONCRETE SYSTE<mark>M</mark>



THE ULTRAGRIND: Propane Concrete Grinder & Polisher

The Ultra Grind professional concrete grinder and polisher eliminates cords and generators. Starter and specialty packages available for chemicals, diamonds, propane vacuum and hand grinders.

THE ULTRAEDGE: Propane Concrete Grinding & Edging

The Ultra Edge propane edger reaches 3" (7.6 cm) under $_{\rm CC}$ 525" (13.3 cm) high shelf and is part of the Ultra Grind 3-pie_{CC} Work Smart cordless grinding, polishing, and edging system.





THE ULTRAVAC: Propane Powered Vacuum

ED)

For dust control when grinding, honing and polishing concrete and terrazzo floors with the WorkSmart Concrete System. HEPA filter and drop down dust pan for dust-free cleanup.

THE GRAND FINALE: Densifier Applicator

Evenly apply concrete densifiers, hardeners and sealers up to 25,000 sqft/ hr. Water solvent-based concrete coating up to 20,000 sqft/hr. No puddles, dry spots or streaking with the battery powered precision release system.





www.aztecproducts.com

merican



The Ultra Grind

WORKSMART[™] CONCRETE SYSTEM

The UltraGrind Propane Concrete Grinder & Polisher



The UltraGrind professional concrete grinder and polisher eliminates cords and generators. Starter and specialty packages available for chemicals, diamonds, propane vacuum and hand grinders.

- Part of the 3-piece WorkSmart cordless grinding, polishing, and edging system
- 8 Gallon (30.3 L) water tank (additional tank available upon request)
- Locking transport wheel
- Adjustable telescoping handle
- Steel body construction
- Removable panel for easy cleaning
- Transport wheel for easy loading and maneuvering
- Green certifications: EPA, CARB, LEED, CE, GS-42
- Optional engine meeting Blue Sky standards



Underside —3 gear drive heads with 4 metal

plates per head



The Ultra Edge

WORKSMART[™] CONCRETE SYSTEM

The Ultra Edge Propane Concrete Edger

Features include:

• Reaches 3" (7.6 cm) under a 5.25" (13.3 cm) high shelf

ID# 041-1

- Grinds and polishes within 1/4" (.6 cm) of walls
- Quick change plate system, Interchangeable with the Ultra Grind
- Uses custom or standard abrasives
- Steel body construction
- Removable panel for easy cleaning
- Optional magnetic attachment system
- Green certifications: EPA, CARB, LEED, CE, GS-42
- Optional engine meeting Blue Sky standards




Additional weight plates for added pressure



The Ultra Vac

WORKSMART[™] CONCRETE SYSTEM

The Ultra Vac Propane Dust Control Vacuum



- 300 CFM
- 136 H2O"/10 Hg"
- 2.75" (7 cm) inlet
- 9 Gallon (34 L) dust pan
- 12V battery start
- 28 sqft (8.5 m 2) microclean filter
- HEPA operation
- Green certifications: EPA, CARB, LEED, CE, GS-42

ID# 040-VAC

Optional engine meeting Blue Sky standards





CONCRETE TRAINING CERTIFICATION







The Aztec Concrete Training Certification program is a comprehensive concrete floor training program to get you Concrete Certified so you can Grind, Polish, Maintain, Refresh, Color, Crack Repair, and Joint Fill Concrete Floors

САШ: (800) 331-1423

EM AIL: m a rketing @a zte cp roducts.com Visit: www.azte cp roducts.com/concrete-training









M ETAL DIAMONDS – 5 SEG | 16-30 GRIT M ETAL DIAMONDS – 10 SEG | 16-30 GRIT M ETAL DIAMONDS – 10 SEG | 50-200 GRIT

Diamond 3" Hybrid Metal Bond Resin Diamonds, 30-Grit Aztec, for use on the Aztec? <u>Ultra Grind</u> or <u>Ultra Edge</u>. The <u>Ultra Grind</u> machine has three (3) heads; each head holds four (4) diamonds; a complete set requires a set of twelve (12) diamond pucks. Diamonds are sold individual.

Approximate lifespan per set: 12,000 sqft, depending on the individual floor.



HYBRID DIAMONDS | 16-50 GRIT

Diamond 3" Metal Bond Diamonds for use on the Aztec <u>UltraGrind</u> OR the Aztec <u>UltraEdge</u>. The <u>UltraGrind</u> machine has three (3) heads; each head holds four (4) diamonds; a complete set requires a set of twelve (12) diamond pucks. Diamonds are sold individual.

Approximate lifespan per set: 25,000 sqft, depending on the individual floor.



RESIN DIAMONDS | 5₀₋3000 GR_{IT}

Resin Diamonds are designed for use on the Aztec UltraGrind, UltraEdge, or Refresher. Resins are sold individually. The UltraGrind and Refresher machines have three (3) heads; each head holds four (4) diamonds; a complete set requires a set of twelve (12) diamond pucks. The Aztec UltraEdge machine has one (1) head; each head holds four (4) diamonds; a complete set requires a set of four (4) diamond pucks.

Approximate lifespan per set: 8,000 sqft, depending on the individual floor.



0" FLOPPY DISCS | 3₀₋800 GR_{IT}

Aztec's 10" resin foppy discs are custom made for use on the Refresher and UltraGrind. Each floppy disc includes six (6) embedded diamond pucks; floppy discs are sold individually. Floppy discs are easily installed with Velcro[®], are more efficient, and will improve labor productivity.

The UltraGrind and Refresher machines have three (3) heads; each machine head holds one (1) floppy; a complete set requires a set of three (3) floppy discs.



CONCRETE CHEMICALS



E KUTGRINDING AGENT | 5 Gallo

Ameripolish[®] EZ-Kut Grinding Agent is a water based, pretreatment, rapid surface preparation agent used for the initial cut on hard, dense concrete and helps with exposing large aggregate faster than dry only or standard wet methods. EZ-Kut also helps by dramatically increasing the productivity of lower-grit diamond tooling. EZ-Kut Grinding Agent achieves this by suspending concrete solids away from the surface for diamond tools to achieve maximum efficiency. This then shortens the project time-line, reduces labor costs and extends the life of diamond tooling. EZ-Kut is also unique in that it can be used in wet and dry grinding methods.



3DHS DENSIFIER | 5 Gallo

3D Hybid Silicate Densifier is three densifiers in one. It improves surface performance and resists the harmful effects of traffic wear and weathering. By having three different sized molecule silicates this product fully penetrates varying densities of concrete regardless of region or hardness. This improves the abrasion resistance for new or aged concrete. 3D HS is ideal for use for exposed and polished concrete, as well as cements with integral color.



3DSPGUARD | 5 Gallo

Ameripolish 3D SP is a breathable semi-penetrating / semi-topical sealer that helps to protect surfaces against stains and etching. 3D SP creates a water resistant barrier that prevents liquids from infiltrating the surface, protecting against staining and color dispersion.



REJUVENATING CLEANER | 10P 32OZ BOTTLE

Ameripolish® Rejuvenating Cleaner is a concentrated multipurpose cleaner that removes daily debris from hard surfaces, as well as reinforces the sealer to extend the life of polished concrete floors. Rejuvenating Cleaner contains no harsh chemicals, and leaves no build-up on the surface. In addition to polished concrete, it is ideal for use on vinyl tile, ceramic tile, terrazzo, wood, and composite materials. It rejuvenates the floor by reapplying trace amounts of densifier and stain resistant additives while you clean with an auto-scrubber. **OZte**®

INDUSTRY ASSOCIATIONS

Aztec is proud to be affiliated with the following industry associations and buying groups:



GREEN CERTIFICATIONS

California Environmental Protection Agency ARRESOURCES BOARD

Lowest emissions in the industry*. Every propane powered engine on Aztec's equipment has been individually tested and is EPA, CARB, LEED and GS42 green certified for indoor use in approved areas, and meet the US green building council LEED IEQ credit 3.4 requirements. Optional engine meeting Blue Sky standards.

Aztec's certifications are on the pages that follow.





California Environmental Protection Agency AID DESOLIDCES BOADD CARB-600V SERIES

CALIFORNIA AIR RESOURCES BOARD AZTEC PRODUCTS INC.

EXECUTIVE ORDER U-U-056-0030 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

500 TWC Polishing, VCT Stripping, Concrete Polishing and O ENGINE CODES/MODELS (rated power in 603 (10.52 kW)	MODEL YEAR	ENGINE FAMIL	DISPLACEMENT (cc)	ENGINE CLA	SS (CNGALNG=compressed/tiquefied natural gas LPG=tk petroleum gas)	(CNG/LNG=compressed/liquefied natural gas_LPG=liquefie	
HOURS EMISSION CONTROL SYSTEMS TTPCAL Equipment, APPLICATION 500 TWC Floor Polishing, Equipment, Vinyl Composition Tile Polishing, VCT Stripping, Concrete Polishing and C Grinding ENGINE CODES/MODELS (rated power in 603 (10.52 kW)	2018 JAPIS.6032NA		603	4-stroke, ≥ 225	i cc LPG	LPG	
500 TWC Floor Polishing Equipment, Vinyl Composition Tile Polishing, VCT Stripping, Concrete Polishing and C Grinding ENGINE CODES/MODELS (rated power in 603 (10.52 kW)					TYPICAL EQUIPMENT APPLICATION		
CODES/MODELS 603 (10.52 kW)			TWC		Floor Polishing Equipment, Vinyl Composition Tile (VCT), Polishing, VCT Stripping, Concrete Polishing and Concrete Grinding		
kilowatt, kW) ABBREVIATIONS: EM-engine modification TWC/OC=three-way/oridizing catalyst WUTWC/WUOC=warm-up TWC/OC 025=copyen sensor H025=heat	CODES/MO (rated pow kilowatt, f	DELS ver in kW)					

ABBREVATIONS: EM-engine molification TWEDDE-three-way outdoing cataryat WEDVECHOUS-waimup worked as a second with the second and the second a

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)	
STANDARD	8.0	549	*	
FAMILY EMISSION LEVEL	• •	•	*	
CERTIFICATION LEVEL	4.8	63	· •	

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _____ day of April 2018.

FO^{1/2} Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division



www.aztecproducts.com



by: azte®

EPA-600V SERIES







CARB-390 SERIES

CALIFORNIA AZTEC PRODUCTS INC. EXECUTIVE ORDER U-U-056-0029 New Off-Road Small Spark-Ignition Engines at or Below 19 Kilowatts

Pursuant to the authority vested in California Air Resources Board by the Health and Safety Code, Division 26, Part 5, Chapters 1 and 2; and

Pursuant to the authority vested in the undersigned by Health and Safety Code Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following engine and emission control systems produced by the manufacturer are certified for use in small off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGI	NE FAMILY DISPLACEMENT (cc)		ENGINE CLASS		FUEL TYPE (CNG/LNG-compressed/liquelled riatural gas LPG=liquelle petroleum gas) LPG	
2018 JAPIS.3902		5.3902NA	3902NA 340, 389		5 oc		
			SPECIAL FEATURES & SION CONTROL SYSTEMS		TYPICAL EQUIPMENT APPLICATION		
1000)	TWC			Floor Polishing Equipment, Vinyl Composition Tile (VCT), Polishing, VCT Stripping, Concrete Polishing and Concrete Grinding		
ENGINE CODES/MODELS (rated power in kilowatt, kW)		390 (6.15 kW), RV340 (7.2 kW)					
BBREVIATIO	ONS: EM-	EM-angine modification TWC/OC-three-wayloxidizing catalyst WUTWC/WUOC-warm-up TWC/OC O2S=oxygen sensor HO2S-heated O2S Ecologiation Alik-secondary air intection PAIR-pulsed AIR MFI-multi port fuel injection SFI=sequential MFI. TBI-throttis bedy fuel injection					

ABBREVATIONS: EM-angine modification TWC/CC-driftee-waysonating charavis with record of the record of the second s

The following are the hydrocarbon plus oxides of nitrogen (HC+NOx), carbon monoxide (CO), and particulate matter (PM) emission standards (Title 13, California Code of Regulations, (13 CCR) Section 2403(b)), and certification emission levels for this engine family in grams per kilowatt-hour (g/kW-hr). Engines within this engine family shall have closed crankcases in conformance with Section 1054.115(a) of the "California Exhaust Emission Standards and Test Procedures for New 2013 and Later Small Off-Road Engines," adopted October 25, 2012.

*=not applicable	HC+NOx (g/kW-hr)	CO (g/kW-hr)	PM (g/kW-hr)
STANDARD	8.0	549	*
FAMILY EMISSION LEVEL	•	•	*
CERTIFICATION LEVEL	2.0	266	•

BE IT FURTHER RESOLVED: That the family emission level(s) (FELs), as applicable, is an emission limit declared by the manufacturer for use in the averaging, banking and trading program and in lieu of an emission standard for certification. It serves as the applicable emission standard for determining compliance of any engine within this engine family under 13 CCR Sections 2403(e)(1) and 2407(a).

BE IT FURTHER RESOLVED: That for the listed engines, the manufacturer has submitted, and the Executive Officer hereby approves, the information and materials to demonstrate certification compliance with 13 CCR Section 2404 (emission control labels) and 13 CCR Sections 2405 and 2406 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

Quarterly reports of engines produced in this engine family for sale in California shall be submitted to the Executive Officer no later than 45 days after the end of each calendar quarter.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this _____ day of April 2018.

JCAnnette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division





by: azte®

EPA-390 SERIES





US GREEN BUILDING COUNCIL LEED REQUIREM ENTS



EQ3.4 requirements



REQEQ3.1r5 | Possible point

Requirements

Implement a program for the use of janitorial equipment that reduces building contaminants and minimizes environmental impact. The cleaning equipment program must require the following:

- Vacuum cleaners are certified by the Carpet and Rug Institute "Green Label" Testing Program for vacuum cleaners and operate with a sound level of less than 70dBA.
- Carpet extraction equipment used for restorative deep cleaning is certified by the Carpet and Rug Institute's "Seal of Approval" Testing Program for deep-cleaning extractors.
- Powered floor maintenance equipment, including electric and battery-powered floor buffers and burnishers, is equipped with vacuums, guards and/or other devices for capturing fine particulates and operates with a sound level of less than 70dBA.
- Propane-powered floor equipment has high-efficiency, low-emissions engines with catalytic converters and mufflers that meet the California Air Resources Board (CARB) or Environmental Protection Agency (EPA) standards for the specific engine size and operate with a sound level of less than 90dBA.
- Automated scrubbing machines are equipped with variable-speed feed pumps and on-board chemical metering to optimize the use of cleaning fluids. Alternatively, the scrubbing machines use only tap water with no added cleaning products.
- Battery-powered equipment is equipped with environmentally preferable gel batteries.
- Powered equipment is ergonomically designed to minimize vibration, noise and user fatigue.
- Equipment is designed with safeguards, such as rollers or rubber bumpers, to reduce potential damage to building surfaces.

Keep a log for all powered cleaning equipment to document the date of equipment purchase and all repair and maintenance activities and include vendor specification sheets for each type of equipment in use.

