



The Industrial Odor Control System That Aggressively Attacks Odors!

About the System

The VaporSHARK™ is designed to provide a simple, safe solution to tough odor problems in a broad spectrum of industries and situations:

- Restoration Projects
- Restaurants/Bars
- Animal Shelters/Veterinary Facilities
- Wherever quick, powerful deodorization is required!

A neutralizing dry vapor is diffused as air passes over replaceable “breathing” membranes to quickly penetrate all porous surfaces, ridding the area of residual malodors.



The VaporSHARK is designed to hold up to five VaporSHARK Membranes. The sealed membranes contain a powerful, proprietary blend of natural oils that are safe, effective, and provide long-lasting neutralization without creating ozone or leaving any residue.

The VaporSHARK does not require evacuation of the treatment area during use and a cleanup/recovery period is not necessary. It will not oxidize materials; damage fabrics, rubber or adhesives, or affect electrical components. ➔

VaporSHARK Combo Special	#90-0950/5
One Model VS.5 plus 5 VaporSHARK 3X membranes	
VaporSHARK VS.5	#90-0950
VaporSHARK Membranes	
Single Pack/3X Industrial	#90-0953
Five-Pack/3X Industrial	#90-0953/5
Five-Pack/Lemon* (for use <u>with</u> 3X)	#90-0953-05/5
Five-Pack/S.O.S. (Smoke Odor Solution)	#90-0953-85/5

TRY US FIRST...WE'RE ALL YOU'LL NEED!

IMPORTANT: This system provides a safe, effective alternative to ozone. It is not recommended for use with ozone-generating equipment.

Product Features

- ➔ Does not use or create ozone.
- ➔ Treats areas up to 50,000 cu. ft.
- ➔ Convenient two-inch O.D. couplings allow connection to standard hoses for precise dry vapor delivery.
- ➔ Uses up to five VaporSHARK 3X Industrial Membranes, available in convenient single packs and 5-packs. Lemon* membrane may be added to enhance 3X fragrance. S.O.S. (Smoke Odor Solution) membranes may be used to treat all types of smoke odors.
- ➔ Typical membrane life is 270 hours.
- ➔ Can be used freestanding or permanently installed to air handling systems.
- ➔ Adjustable external air inlet control.
- ➔ Durable aluminum housing.
- ➔ Six-foot grounded power cord.
- ➔ CSA/CUL approved.
- ➔ .8/.7 amps, 50/60 Hz., 120 volts, 53 watts.
- ➔ Comfort handle for convenient transport.
- ➔ Heavy-duty dual hasps with locking capability.
- ➔ Approximate unit weight: 13 lbs.
- ➔ Approximate unit dimensions: 16"H x 8"W x 17"L.
- ➔ Five-year limited warranty.

TREATS ATMOSPHERE, CONTENTS AND STRUCTURE SIMULTANEOUSLY!

TESTED AND PROVEN BY RESTORATION COMPANIES WORLDWIDE FOR WATER DAMAGE; PLASTIC, WOOD AND FOOD PROTEIN FIRES; SKUNK; BIO-RECOVERY; MORGUE AND OTHER DIFFICULT ODOR CHALLENGES.

Use Xactimate codes:
CLN DODRM,
CLN DODRME
and CLN DODRMEM.